

## REFERENCES

- Ahmad, A., Rahman, M. Y. A., Harun, H., Su'ait, M. S., & Yarmo, M. A. (2012). Preparation and Characterization of 49% Poly(Methyl Methacrylate) Grafted Natural Rubber (MG49)-Stannum (IV) Oxide (SnO<sub>2</sub>)-Lithium Salt Based Composite Polymer Electrolyte. *International Journal of Electrochemical Science*, 7(9), 8309–8325.
- Arya, A., & Sharma, A. L. (2017). Polymer electrolytes for lithium ion batteries: a critical study. In *Ionics* (Vol. 23, Issue 3). Ionics. <https://doi.org/10.1007/s11581-016-1908-6>.
- Asif, A., Huang, C., & Shi, W. (2004). Structure-property study of waterborne, polyurethane acrylate dispersions based on hyperbranched aliphatic polyester for UV-curable coatings. *Colloid and Polymer Science*, 283(2), 200–208. <https://doi.org/10.1007/s00396-004-1123-2>.
- Aziz, S. B. (2013). Li<sup>+</sup> ion conduction mechanism in poly ( $\epsilon$ -caprolactone)-based polymer electrolyte. *Iranian Polymer Journal (English Edition)*, 22(12), 877–883. <https://doi.org/10.1007/s13726-013-0186-7>.
- Bahnini, I., Rivette, M., Rechia, A., Siadat, A., & Elmesbahi, A. (2018). Additive manufacturing technology: the status, applications, and prospects. *International Journal of Advanced Manufacturing Technology*, 97(1–4), 147–161. <https://doi.org/10.1007/s00170-018-1932-y>.
- Cai, X., Luo, Y., Liu, B., & Cheng, H. M. (2018). Preparation of 2D material dispersions and their applications. *Chemical Society Reviews*, 47(16), 6224–6266. <https://doi.org/10.1039/C8CS00254A>.
- Calignano, F., Manfredi, D., Ambrosio, E. P., Biamino, S., Lombardi, M., Atzeni, E., Salmi, A., Minetola, P., Iuliano, L., & Fino, P. (2017). Overview on additive manufacturing technologies. *Proceedings of the IEEE*, 105(4), 593–612. <https://doi.org/10.1109/JPROC.2016.2625098>.
- Chai, K. L., Noor, I. M., Aung, M. M., Abdullah, L. C., & Kufian, M. Z. (2020). Non-edible oil based polyurethane acrylate with tetrabutylammonium iodide gel polymer electrolytes for dye-sensitized solar cells. *Solar Energy*, 208(May), 457–468. <https://doi.org/10.1016/j.solener.2020.08.020>.
- Chang, P., Mei, H., Zhou, S., Dassios, K. G., & Cheng, L. (2019). 3D printed electrochemical energy storage devices. *Journal of Materials Chemistry A*, 7(9), 4230–4258. <https://doi.org/10.1039/C8TA11860D>.
- Chen, Z., Xu, N., Li, W., Zhao, R., Dong, Y., Liu, J., Su, C., Wang, J., & Zhang, C. (2019).

- Effect of trace hydrofluoric acid in a LiPF<sub>6</sub> electrolyte on the performance of a Li-organic battery with an N-heterocycle based conjugated microporous polymer as the cathode. *Journal of Materials Chemistry A*, 7(27), 16347–16355. <https://doi.org/10.1039/c9ta01810g>.
- Cheng, M., Jiang, Y., Yao, W., Yuan, Y., Deivanayagam, R., Foroozan, T., Huang, Z., Song, B., Rojaee, R., Shokuhfar, T., Pan, Y., Lu, J., & Shahbazian-Yassar, R. (2018). Elevated-Temperature 3D Printing of Hybrid Solid-State Electrolyte for Li-Ion Batteries. *Advanced Materials*. <https://doi.org/10.1002/adma.201800615>.
- Digar, M., Hung, S. L., Wang, H. L., Wen, T. C., & Gopalan, A. (2001). Study of ionic conductivity and microstructure of a cross-linked polyurethane acrylate electrolyte. *Polymer*, 43(3), 681–691. [https://doi.org/10.1016/S0032-3861\(01\)00655-3](https://doi.org/10.1016/S0032-3861(01)00655-3).
- Digar, M. L., Hung, S. L., Wen, T. C., & Gopalan, A. (2002). Studies on cross-linked polyurethane acrylate-based electrolyte consisting of reactive vinyl/divinyl diluents. *Polymer*, 43(5), 1615–1622. [https://doi.org/10.1016/S0032-3861\(01\)00737-6](https://doi.org/10.1016/S0032-3861(01)00737-6).
- Digar, Mohanlal, & Wen, T. C. (2000). Ionic conductivity and morphological study of a thermoplastic polyurethane based electrolyte comprising of mixed soft segments. *Polymer Journal*, 32(11), 921–931. <https://doi.org/10.1295/polymj.32.921>.
- Fenton, D. E., Parker, J. M., & Wright, P. V. (1973). Complexes of alkali metal ions with poly(ethylene oxide). *Polymer*, 14(11), 589. [https://doi.org/10.1016/0032-3861\(73\)90146-8](https://doi.org/10.1016/0032-3861(73)90146-8).
- Feuillade, G., & Perche, P. (1975). Ion-conductive macromolecular gels and membranes for solid lithium cells. *Journal of Applied Electrochemistry* 1975 5:1, 5(1), 63–69. <https://doi.org/10.1007/BF00625960>.
- Gibson, I., Rosen, D., & Stucker, B. (2015). Additive manufacturing technologies: 3D printing, rapid prototyping, and direct digital manufacturing, second edition. In *Additive Manufacturing Technologies: 3D Printing, Rapid Prototyping, and Direct Digital Manufacturing, Second Edition*. Springer New York. <https://doi.org/10.1007/978-1-4939-2113-3>.
- Harshlata, Mishra, K., & Rai, D. K. (2021). Studies on ionic liquid based nanocomposite gel polymer electrolyte and its application in sodium battery. *Materials Science and Engineering: B*, 267(January), 115098. <https://doi.org/10.1016/j.mseb.2021.115098>.
- Hassoun, J., & Scrosati, B. (2015). Review — Advances in Anode and Electrolyte Materials for the Progress of Lithium-Ion and beyond Lithium-Ion Batteries. 162(14), 2582–2588. <https://doi.org/10.1149/2.0191514jes>.
- He, Y., Chen, S., Nie, L., Sun, Z., Wu, X., & Liu, W. (2020). Stereolithography Three-Dimensional Printing Solid Polymer Electrolytes for All-Solid-State Lithium Metal

- Batteries. *Nano Letters*, 20(10), 7136–7143.  
<https://doi.org/10.1021/acs.nanolett.0c02457>.
- Imperiyka, M., Ahmad, A., Hanifah, S. A., & Rahman, M. Y. A. (2014). Preparation and characterization of polymer electrolyte of glycidyl methacrylate-methyl methacrylate-LiClO<sub>4</sub> plasticized with ethylene carbonate. *International Journal of Polymer Science*, 2014. <https://doi.org/10.1155/2014/638279>.
- ISO/ASTM. (2013). Additive Manufacturing - General Principles Terminology (ASTM52900). *Rapid Manufacturing Association*, 10–12.  
<https://doi.org/10.1520/F2792-12A.2>.
- Johan, M. R., Shy, O. H., Ibrahim, S., Mohd Yassin, S. M., & Hui, T. Y. (2011). Effects of Al<sub>2</sub>O<sub>3</sub> nanofiller and EC plasticizer on the ionic conductivity enhancement of solid PEO-LiCF<sub>3</sub>SO<sub>3</sub> solid polymer electrolyte. *Solid State Ionics*, 196(1), 41–47.  
<https://doi.org/10.1016/j.ssi.2011.06.001>.
- Kai Ling, C., Aung, M. M., Rayung, M., Chuah Abdullah, L., Lim, H. N., & Mohd Noor, I. S. (2019). Performance of Ionic Transport Properties in Vegetable Oil-Based Polyurethane Acrylate Gel Polymer Electrolyte. *ACS Omega*, 4(2), 2554–2564.  
<https://doi.org/10.1021/acsomega.8b02100>.
- Kartha, T. R., & Mallik, B. S. (2020). Revisiting LiClO<sub>4</sub> as an electrolyte for Li-ion battery: Effect of aggregation behavior on ion-pairing dynamics and conductance. *Journal of Molecular Liquids*, 302, 112536. <https://doi.org/10.1016/j.molliq.2020.112536>.
- Khiar, A. S. A. A., Puteh, R., & Arof, A. K. A. (2006). Conductivity studies of a chitosan-based polymer electrolyte. *Physica B: Condensed Matter*, 373(1), 23–27.  
<https://doi.org/10.1016/j.physb.2005.10.104>.
- Kim, H. N., Kim, K. G., Jeong, Y. U., & Kim, S. Y. (2020). Double-crosslinked polyurethane acrylate for highly conductive and stable polymer electrolyte. *Polymers*, 12(11), 1–10. <https://doi.org/10.3390/polym12112557>.
- Kotobuki, M., Suzuki, Y., Munakata, H., Kanamura, K., Sato, Y., Yamamoto, K., & Yoshida, T. (2010). Fabrication of Three-Dimensional Battery Using Ceramic Electrolyte with Honeycomb Structure by Sol-Gel Process. *Journal of The Electrochemical Society*, 157(4), A493. <https://doi.org/10.1149/1.3308459>.
- Lain, M. J., Brandon, J., & Kendrick, E. (2019). Design strategies for high power vs. High energy lithium ion cells. *Batteries*, 5(4). <https://doi.org/10.3390/batteries5040064>.
- Larsson, F., Andersson, P., Blomqvist, P., & Mellander, B. E. (2017). Toxic fluoride gas emissions from lithium-ion battery fires. *Scientific Reports*, 7(1), 1–13.  
<https://doi.org/10.1038/s41598-017-09784-z>.

- Lee, E. J., Park, K. H., Lee, Y. H., Kim, K. G., Jeong, Y. U., Kim, S. Y., & Kim, H. Do. (2017). Poly(urethane acrylate)-based gel polymer films for mechanically stable, transparent, and highly conductive polymer electrolyte applications. *Journal of Applied Polymer Science*, 134(26), 1–9. <https://doi.org/10.1002/app.45009>.
- Lewis, J. A. (2006). Direct ink writing of 3D functional materials. *Advanced Functional Materials*, 16(17), 2193–2204. <https://doi.org/10.1002/adfm.200600434>.
- Liao, F., Zeng, X. R., Li, H. Q., Lai, X. J., & Zhao, F. C. (2012). Synthesis and properties of UV curable polyurethane acrylates based on two different hydroxyethyl acrylates. *Journal of Central South University of Technology (English Edition)*, 19(4), 911–917. <https://doi.org/10.1007/S11771-012-1092-4/METRICS>.
- Licoccia, S., Trombetta, M., Capitani, D., Proietti, N., Romagnoli, P., & Di Vona, M. L. (2005). ATR-FTIR and NMR spectroscopic studies on the structure of polymeric gel electrolytes for biomedical applications. *Polymer*, 46(13), 4670–4675. <https://doi.org/10.1016/j.polymer.2005.03.078>.
- Long, J. W., Dunn, B., Rolison, D. R., & White, H. S. (2004). Three-dimensional battery architectures. *Chemical Reviews*, 104(10), 4463–4492. <https://doi.org/10.1021/cr020740l>.
- Long, L., Wang, S., Xiao, M., & Meng, Y. (2016). Polymer electrolytes for lithium polymer batteries. *Journal of Materials Chemistry A: Materials for Energy and Sustainability*, 4, 10038–10069. <https://doi.org/10.1039/C6TA02621D>.
- Lv, P., Yang, J., Liu, G., Liu, H., Li, S., Tang, C., Mei, J., Li, Y., & Hui, D. (2017). Flexible solid electrolyte based on UV cured polyurethane acrylate/succinonitrile-lithium salt composite compatibilized by tetrahydrofuran. *Composites Part B: Engineering*, 120, 35–41. <https://doi.org/10.1016/j.compositesb.2017.03.060>.
- Lyu, Z., Lim, G. J. H., Koh, J. J., Li, Y., Ma, Y., Ding, J., Wang, J., Hu, Z., Wang, J., Chen, W., & Chen, Y. (2021). Design and Manufacture of 3D-Printed Batteries. *Joule*, 5(1), 89–114. <https://doi.org/10.1016/j.joule.2020.11.010>.
- Mauger, A., Julien, C. M., Paoletta, A., Armand, M., & Zaghbi, K. (2018). A comprehensive review of lithium salts and beyond for rechargeable batteries: Progress and perspectives. *Materials Science and Engineering R: Reports*, 134(March), 1–21. <https://doi.org/10.1016/j.mser.2018.07.001>.
- Maurel, A., Armand, M., Grugeon, S., Fleutot, B., Davoisne, C., Tortajada, H., Courty, M., & Panier, S. (2020). Poly ( Ethylene Oxide ) LiTFSI Solid Polymer Electrolyte Filaments for Fused Deposition Modeling Three-Dimensional Printing Poly ( Ethylene Oxide ) – LiTFSI Solid Polymer Electrolyte Filaments for Fused Deposition Modeling Three-Dimensional Printing. <https://doi.org/10.1149/1945-7111/ab7c38>.

- McOwen, D. W., Xu, S., Gong, Y., Wen, Y., Godbey, G. L., Gritton, J. E., Hamann, T. R., Dai, J., Hitz, G. T., Hu, L., & Wachsman, E. D. (2018). 3D-Printing Electrolytes for Solid-State Batteries. *Advanced Materials*, 30(18), 1–7. <https://doi.org/10.1002/adma.201707132>.
- Mustapa, S. R., Aung, M. M., Ahmad, A., Mansor, A., & TianKhoon, L. (2016). Preparation and characterization of Jatropha oil-based Polyurethane as non-aqueous solid polymer electrolyte for electrochemical devices. *Electrochimica Acta*, 222, 293–302. <https://doi.org/10.1016/j.electacta.2016.10.173>.
- Naiwi, T. S. R., Aung, M. M., Ahmad, A., Rayung, M., Su'ait, M. S., Yusof, N. A., & Lae, K. Z. W. (2018). Enhancement of plasticizing effect on bio-based polyurethane acrylate solid polymer electrolyte and its properties. *Polymers*, 10(10). <https://doi.org/10.3390/polym10101142>.
- Pan, L. (2018). Printing 3D gel polymer electrolyte in Li-ion microbattery using stereolithography. *35th Annual International Battery Seminar and Exhibit 2018*, 2(9), 871–883. <https://doi.org/10.1149/2.0651709jes>.
- Pang, Y., Cao, Y., Chu, Y., Liu, M., Snyder, K., MacKenzie, D., & Cao, C. (2020). Additive Manufacturing of Batteries. *Advanced Functional Materials*, 30(1), 1–22. <https://doi.org/10.1002/adfm.201906244>.
- Pradhan, D. K., Choudhary, R. N. P., & Samantaray, B. K. (2008). Studies of dielectric relaxation and AC conductivity behavior of plasticized polymer nanocomposite electrolytes. *International Journal of Electrochemical Science*, 3(5), 597–608.
- Ragones, H., Menkin, S., Kamir, Y., Gladkikh, A., Mukra, T., Kosa, G., & Golodnitsky, D. (2018). Towards smart free form-factor 3D printable batteries. *Sustainable Energy and Fuels*, 2(7), 1542–1549. <https://doi.org/10.1039/c8se00122g>.
- Ramesh, S., Liew, C. W., Morris, E., & Durairaj, R. (2010). Effect of PVC on ionic conductivity, crystallographic structural, morphological and thermal characterizations in PMMA-PVC blend-based polymer electrolytes. *Thermochimica Acta*, 511(1–2), 140–146. <https://doi.org/10.1016/j.tca.2010.08.005>.
- Ren, T., Luo, Y., Huang, X., & Tang, X. (2003). Synthesis and characterization of novel crosslinked polyurethane-acrylate electrolyte. *Journal of Applied Polymer Science*, 89(2), 340–348. <https://doi.org/10.1002/app.11786>.
- Saikia, D., Chen, Y. H., Pan, Y. C., Fang, J., Tsai, L. D., Fey, G. T. K., & Kao, H. M. (2011). A new highly conductive organic-inorganic solid polymer electrolyte based on a di-ureasil matrix doped with lithium perchlorate. *Journal of Materials Chemistry*, 21(28), 10542–10551. <https://doi.org/10.1039/c1jm11177a>.
- Samsudin, A. S., Khairul, W. M., & Isa, M. I. N. (2012). Characterization on the potential

- of carboxy methylcellulose for application as proton conducting biopolymer electrolytes. *Journal of Non-Crystalline Solids*, 358(8), 1104–1112. <https://doi.org/10.1016/j.jnoncrsol.2012.02.004>.
- Santhosh, P., Vasudevan, T., Gopalan, A., & Lee, K. P. (2006). Preparation and properties of new cross-linked polyurethane acrylate electrolytes for lithium batteries. *Journal of Power Sources*, 160(1), 609–620. <https://doi.org/10.1016/j.jpowsour.2006.01.091>.
- Shamsuddin, L., Noor, I. M., Albinsson, I., Mellander, B. E., & Arof, A. K. (2017). Perovskite solar cells using polymer electrolytes. *Molecular Crystals and Liquid Crystals*, 655(1), 181–194. <https://doi.org/10.1080/15421406.2017.1362889>.
- Sim, L. H., Gan, S. N., Chan, C. H., & Yahya, R. (2010). ATR-FTIR studies on ion interaction of lithium perchlorate in polyacrylate/poly(ethylene oxide) blends. *Spectrochimica Acta - Part A: Molecular and Biomolecular Spectroscopy*, 76(3–4), 287–292. <https://doi.org/10.1016/j.saa.2009.09.031>.
- Strmcnik, D., Castelli, I. E., Connell, J. G., Haering, D., Zorko, M., Martins, P., Lopes, P. P., Genorio, B., Østergaard, T., Gasteiger, H. A., Maglia, F., Antonopoulos, B. K., Stamenkovic, V. R., Rossmeisl, J., & Markovic, N. M. (2018). Electrocatalytic transformation of HF impurity to H<sub>2</sub> and LiF in lithium-ion batteries. *Nature Catalysis*, 1(4), 255–262. <https://doi.org/10.1038/s41929-018-0047-z>.
- Tang, Y., Wu, K., Yu, S., Chen, J., Ding, X., Rao, L., & Li, Z. (2020). Bioinspired high-scattering polymer films fabricated by polymerization-induced phase separation. *Optics Letters*, 45(10), 2918. <https://doi.org/10.1364/ol.390639>.
- Tuan Naiwi, T. S. R., Aung, M. M., Rayung, M., Ahmad, A., Chai, K. L., Wun Fui, M. L., Mohd Tarmizi, E. Z., & Abdul Aziz, N. A. (2022). Dielectric and ionic transport properties of bio-based polyurethane acrylate solid polymer electrolyte for application in electrochemical devices. *Polymer Testing*, 106, 107459. <https://doi.org/10.1016/j.polymertesting.2021.107459>.
- Whba, R. A. G., TianKhoon, L., Su'ait, M. S., Rahman, M. Y. A., & Ahmad, A. (2020). Influence of binary lithium salts on 49% poly(methyl methacrylate) grafted natural rubber based solid polymer electrolytes. *Arabian Journal of Chemistry*, 13(1), 3351–3361. <https://doi.org/10.1016/j.arabjc.2018.11.009>.
- Xu, K. (2004). Nonaqueous liquid electrolytes for lithium-based rechargeable batteries. *Chemical Reviews*, 104(10), 4303–4417. <https://doi.org/10.1021/cr030203g>.
- Yao, P., Yu, H., Ding, Z., Liu, Y., Lu, J., Lavorgna, M., Wu, J., & Liu, X. (2019). Review on Polymer-Based Composite Electrolytes for Lithium Batteries. *Frontiers in Chemistry*, 7(August), 1–17. <https://doi.org/10.3389/fchem.2019.00522>.
- Ye, L., & Feng, Z. (2010). Polymer electrolytes as solid solvents and their applications. In

*Polymer Electrolytes: Fundamentals and Applications* (pp. 550–582). Elsevier Ltd.  
<https://doi.org/10.1533/9781845699772.2.550>.

Zhang, F., Wei, M., Viswanathan, V. V., Swart, B., & Shao, Y. (2017). 3D printing technologies for electrochemical energy storage. *Nano Energy*, 40(August), 418–431.  
<https://doi.org/10.1016/j.nanoen.2017.08.037>.

Zhang, J., Sun, B., Huang, X., Chen, S., & Wang, G. (2014). Honeycomb-like porous gel polymer electrolyte membrane for lithium ion batteries with enhanced safety. *Scientific Reports*, 4(1), 1–7. <https://doi.org/10.1038/srep06007>.

